

Medium Industrial

Heavy Industrial

Multiprocess 5 Pro 261M

The Canaweld **Multiprocess 5 PRO 261M** is a high-performance, heavy-duty multiprocess welding machine, designed for precision, power, and durability in industrial welding applications. This Canadian-made welding machine supports MIG (Manual & Synergic), MIG Brazing, Flux-Cored, TIG DC (No HF), and Stick welding, making it one of the most versatile and reliable welding solutions on the market.

With one of the highest duty cycles in its class in North America, it delivers 260A at 60% duty cycle and 230A at 100% duty cycle (at 104°F/40°C). Engineered for heavy-duty industrial performance, this Canaweld welding machine provides exceptional arc stability while remaining portable and easy to move, making it ideal for welding workshops, job sites, and field operations.

Canaweld offers North America's only 4-year warranty, ensuring unmatched reliability and superior performance. The heavy-duty 4-roll wire feeder provides smooth, consistent wire feeding, enhancing welding efficiency and precision.

Built to handle all metals, including aluminum, stainless steel, and alloys, the Canaweld Multiprocess 5 PRO 261M sets a new industry standard in welding innovation, efficiency, and durability. This industrial multiprocess welder is the ultimate choice for professional welders seeking high-quality, Canadian-made welding equipment.

Features

- 5-in-1 Functionality: Supports MIG Synergic/ MIG Manual, MIG Brazing, Flux-Cored, TIG DC (without HF), and Stick Welding, offering maximum flexibility for diverse applications.
- Rugged Yet Lightweight Design: Metal face panel with flip doors for easy
 access and enhanced durability, ideal for on-site and field welding.
- **Versatile Polarity Options:** Manual switching between gas and gasless wires, Stick electrodes, and Lift TIG welding for added convenience.
- Innovative Wind Tunnel System: Minimizes dust and debris intake, increasing durability and extending machine lifespan.
- Auto-Control Fan Cooling: Activates only when necessary, reducing dust buildup, noise, and overheating risks, while increasing power supply efficiency and fan longevity.
- Extreme Duty Cycle Testing: Designed for continuous operation at 104°F (40°C) and 50% humidity, ensuring superior reliability in harsh conditions.
- Advanced Heat Control: Reduces distortion while maintaining consistent penetration for high-quality welds.
- Clean Welds with Minimal Spatter: Optimized arc control produces stronger, cleaner joints.
- User-Friendly LCD Display: Provides a clear, intuitive interface, allowing quick adjustments for both novice and professional welders.
- Program Memory: Save and recall up to 10 favorite settings, improving efficiency and streamlining workflow.
- 4-Year Warranty: Backed by Canaweld's industry-leading support, ensuring long-term reliability.
- Canaweld Professional Wire Feeder: Ensures precise and consistent wire feeding, optimizing weld quality and reducing feed-related issues.















PROCESSES











MIG Manual/Synergic



MIG Brazing



Flux Cored



TIG DC (No HF)



Stick

- Comprehensive MIG Controls: Full control over wire speed, voltage, trigger mode (2T/4T), burnback, pre-flow, post-flow, and slow feed, with additional inductance adjustment for optimal tuning.
- **Spool Gun Mode:** Enhances performance when welding soft metals like aluminum with thin-gauge wires, ensuring smooth feeding and clean welds.
- MIG Synergic Technology: Automatically selects and adjusts optimal welding parameters for MIG, MIG Brazing, and Flux-Cored welding, making setup effortless while delivering superior performance for welders of all skill levels.
- High-Performance MIG Output: 260A at 60% duty cycle and 230A at 100% duty cycle (at 104°F/40°C), ideal for demanding industrial environments.
- Arc Force Control: Automatically adjusts arc dynamics to enhance arc stability, maintain a steady arc, and prevent electrode sticking, ensuring a smoother welding experience.
- Voltage Reduction Device (VRD): A built-in safety feature that lowers open-circuit voltage (OCV) to minimize electric shock risks, while ensuring optimal voltage when welding.



Multiprocess 5 Pro 261M

Mult	i process 5	Pro M261 T	echnical S	pecification	on		
Process	Unit	MIG/Flux cored	TIG DC (Lift Arc)	Stick Electrode	MIG /Flux cored	TIG DC (Lift Arc)	Stick Electrode
Input Voltage, Single Phase, 50/60 Hz	V	2	08 to 240(±10	0%)	105	5 to 120(±10%)
Primary Current@Max Welding Current	Α	37	27	38.5	37	26.5	35
Maximum Primary Effective Current (I1 eff max)	Α	30	27	30	27.5	26.5	27.5
Programming and Saving Parameters)				Up to 1	0 JOBs		
Technology of Adjustment (Manual/Synergic)	Manual or Synergic						
Welding Current Range	Α	30 – 260	10 – 250	20 – 250	30 – 160	10 – 150	20 – 130
Duty Cycle @ Rated Current in 104° F (40° C)	Α	60%@260	100%@250	60%@250	30%@160	100%@150	60%@130
Welding Current @ 100% Duty Cycle in 104° F(40° C)	Α	230	250	210	130	150	110
Welding Current @ 60% Duty Cycle in 104° F(40° C)	Α	260	-	250	160	-	130
Open Circuit Voltage	V		99			99	
Solid Steel Wire Size Range	inch (mm)	0.030 -	- 0.045 (0.8 –	1.2)	0.030 - 0.040 (0.8 - 1)		- 1)
Stainless steel Wire Size Range	inch (mm)	0.035 -	- 0.045 (0.9 –	1.2) 0.035 – 0.040 (0.9 – 1.0)			1.0)
Flux-cored Wire Size Range	inch (mm)	0.035 -	- 0.045 (0.9 –	1.2)	2) 0.035 – 0.040 (0.8 – 1.0)		
Aluminum Wire Size Range	inch (mm)	0.035 - 0.045 (0.9 - 1.2)			0.035 - 0.040 (0.9 - 1.2)		
Max Wire Feeder speed	ipm (m/min)	944 (24)					
Wire Feeder Mechanism Material	Mechanism Material Metal						
Wire Spool Size	inch (mm)	8 or 12 inch (203 or 305 mm)					
Weight	lb	59.5 (27 Kg)					
Dimensions Including Handle (D, W, H)	inch (mm)	26 x 10.2 x 19.2 inch (660 x 260 x 490 mm)					

CANAWELD RESERVES THE RIGHTS OF CHANGING THE SPECIFICATION WITHOUT NOTICE



Multiprocess 5 Pro 261M





The Canaweld wire feeder for welding machines is designed for heavy-duty performance and high precision. It features a selectable two- or four-roll system, allowing for easy conversion between the two configurations. This flexibility ensures reliable, trouble-free, and consistent wire feeding for all types of welding wires, including solid, flux-cored, and aluminum wires

Quality Control at Canaweld

At Canaweld, we stand behind our machines with a 4-year warranty and offer up to 5 years of coverage on select parts. Our machines undergo rigorous testing, including evaluations at 40°C (104°F) with 50% humidity and extreme conditions ranging from 50°C (122°F) to 0°C (32°F), ensuring reliable performance in any climate.

Our computerized testing systems continuously monitor and record parameters to ensure top-tier operation. Designed and manufactured in Toronto, Ontario, Canada, all Canaweld machines are thoroughly inspected by CSA-certified experts before shipping.

•CSA Certification: Canaweld machines are CSA certified, ensuring they meet Canadian safety and quality regulations. This guarantees that products are tested for safety, performance, and durability.

Ontario Made Certification:

Designed, assembled, and tested in Canada, Canaweld is proud to be an Ontario Made company, offering local craftsmanship and trusted Canadian quality.

•Thorough Testing Process:

Each machine is tested for Routine and type tests, along with all electrical safety standards, are conducted according to IEC, CSA, and other international standards.

All machines are tested under strict conditions, which is why Canaweld proudly offers a four-year warranty on its products — longer than what many competitors provide.





Multiprocess 5 Pro 261M



Available Models:

- Multi process 5 Pro M261- Silver Package (PLB7580172)
- Multi process 5 Pro M261- Silver Plus Package (PLB7580169)
- Multi process 5 Pro M261- Gold Package (PLB7580173)
- Multi process 5 Pro M261- ALUMINUM Package (PLB7580178)

Multi process 5 Pro M261- Silver Package

A V. V.	hat		
_ ' A ' /			

Multi process 5 Pro M261- Silver Package (PLB7580172)

ITEM	QTY	Description	PART NO.	
Ground ClampSet	1	Ground Clamp Set 230-270 A including:10 ft. Welding Cable AWG 2 (33.6 mm),Cable Plug 35	ALP2280505	94
Electrode HolderSet	1	Electrode holder Set 230-270 A including: 10ft. welding cable AWG 2 (33.6 mm), Cable Plug 35,	ALP2280099	
TIGTorch M300Series	1	Tweco® style M300 TE, Euro termination, 15 Ft.	CWGPGTW300-15E	000
Gas Welding Hose	1	1/4"Argon Gas Hose, 10 ft. inculding quick connector	TLJ1080188	0
	2	Feed Roll 37MM For Haro Drive (1.0+1.2)+ Red+Orange	CW211012	එහි
	2	Set of 2 Feed Rolls 0.035-0.045 Inch Or 0.9-1.1 mm V Groove (Hard Wire)	CW210911	∞
MIG Drive Rolls Set	2	Feed Roll 37MM For Haro Drive (1.0+1.2 MM)+ Red+Orange	CW241012	එහි
	2	Set of 2 Pressure Rolls flat 0.035-0.045 Inch Or 0.9-1.1 mm (Hard Wire)	CW240911	∞
	4	Feed Roll 37MM Twin For Alu Wire (1.2+1.6 MMYellow+Orange)	CW261216	9
AdjustableNozzle Insulator	1	MIGAdjustable Nozzle Insulator, Tweco® style, 300 & 400AM	CWU34A	
	5	ContactTip 0.030 inch (0.8 mm)		
	5	ContactTip 0.035 inch (0.9 mm)		
MIG Gun Tweco®Style Consumable Kits	5	ContactTip 0.040 inch (1.0 mm)	ALPCON4001	≫
	5	ContactTip 0.045 inch (1.2 mm)		
	1	Mig Gun Nozzle -Push On,Adjustable tweco® style		
Spool HolderAdapter	1	Spool HolderAdapter 12"(30cm)To 8"(20cm)	CGA2890928	○
Argon/CO2 Regulator	1	UL-Approved MV250Series,SingleStage ForArgon/CO2,Mix	CW-RMV-250-30LM-AR	90



Multiprocess 5 Pro 261M





Multi process 5 Pro M261- Silver Plus Package

Multi process 5 Pro M261- Gold Package

Upgrade to "Silver Plus" and get additional:

Multi process 5 Pro M261- Silver Plus Package (PLB7580169)

ITEM	QTY	Description	PART NO.	
SWIVEL CASTER Package for MIG Machines	1		TGL2280100	1

Upgrade to "Gold" and get additional:

Multi process 5 Pro M261- Gold Package (PLB7580173)

ITEM	QTY	Description	PART NO.	
TIGTorchAirCooled(26Series)	1	Premium TIG Torch,Air cooled, 200AMP, 9 Pin, 12 ft	CWSG26FX-S1-12-SL-GS4-9PIN	3
	1	Collet 1/16"(1.6 mm)		
	1	Collet 3/32"(2.4 mm)	ALPTORCHCON26	
TIG ConsumableKit	1	Collet body 1/16"(1.6 mm)		
	1	Collet body 3/32"(2.4 mm)		
	1	TIG CERAMIC CUP#8, 12.5 mm		-X"
	1	TIG CERAMIC CUP#7, 11 mm		
	1	BACK CAPSMALL		
	1	BACK CAP MEDIUM		
TIGTungstenElectrode	1	Mix Of Six Tungsten Electrode (CWMIX6)	CTE500-RGB-116332	



Multiprocess 5 Pro 261M



Multi process 5 Pro M261- ALUMINUM Package

Upgrade to "Aluminum" and get additional:

Multi process 5 Pro M261- ALUMINUM Package (PLB7580178)

ITEM	QTY	Description	PART NO.	
Spool Gun SM300 Series	1	Spool Gun SM 300 TE, TWECO @Style Head, Euro Style Termination	CWGPG-PLSPTW300-24-P10-60TE	Ó
Spool Gun Drive Rolls	1	Drive Roll , U Groove forAluminum 0.030" (0.8 mm)	CWUGP7020W-08U	0
Spool Gun Drive Rolls	1	Drive Roll , V Groove for Solid wire 0.030" (0.8 mm)	CWUGP7020W-08	0
Spool Gun Drive Rolls	1	Drive Roll, U Groove FORAluminum wire 0.040" (1.0 mm)	CWUGP7020W-10U	6
Spool Gun Drive Rolls	1	Drive Roll , V Groove for Solid wire 0.035" (0.9 mm)	CWUGP7020W-09	0
MIG Gun Tweco® Style Consumable Kit	1	MIG TORCH Tweco® Style 300ASpool Gun Consumable Set/ Aluminum Package	ALPCON4001AL	



Multiprocess 5 Pro 261M



Applications: Ideal for industries where weld quality and appearance matter most, including:

- · Aerospace Industry
- · Automotive (Parts and Body Manufacturing)
- · Heavy and Medium-Duty Fabrication
- · Boat and Yacht Construction
- · Food and Beverage Equipment Manufacturing
- · Pharmaceutical and Medical Equipment
- · Pressure Vessels
- · Civil and General Construction
- · Railcar and Train Manufacturing
- Service and Work Trucks
- · Vocational Training Schools
- Plumbing and HVAC Systems
- Mechanical Contractors
- Installation
- Restoring
- · Maintenance and repair-field operation
- Farm and Ranch

Weldable Metals:

- Steel
- Stainless Steel
- Aluminium
- · Chrome Moly
- Titanium
- Copper





Multiprocess 5 Pro 261M

The machine has a built-in 21.7 x 6.3 x 6.1-inch storage compartment.

OPTIONAL ACCESSORIE	S	
PRODUCT	PART NO.	
Spool Gun CST251, 9 Pin-10ft (3 Meter), 0.030"-0.040" / (0.8-1.0 mm)	CWICL08131	3
Spool Gun CST251, 9 Pin-13ft (4 Meter), 0.030"-0.040" / (0.8-1.0 mm)	CWICL08141	Š
MIG Spool Gun SMH360 Series – Binzel Model	CWGPG-PGSP360A-24-P10-60BE	· ·
MIG Torch, Tweco® style M300 TE, Euro termination, 15 Ft	CWGPGTW300-15E	Ö
Electrode holder Set , 400A, 20ft, Cable SizeAWG 1/0 (42.4 mm), Cable Plug 35	ALP1980468	0
Electrode holder Set , 400A, 30ft, Cable SizeAWG 1/0 (42.4 mm), Cable Plug 35	ALP1980469	0
Electrode holder Set , 400A, 50ft, Cable SizeAWG 1/0 (42.4 mm), Cable Plug 35	ALP1980470	
Ground Clamp Set , 400A, 20ft, Cable SizeAWG 1/0 (42.4 mm), Cable Plug 35	ALP1980459	9
Ground Clamp Set , 400A, 30ft, Cable SizeAWG 1/0 (42.4 mm), Cable Plug 35	ALP1980471	9
Ground Clamp Set , 400A, 50ft, Cable SizeAWG 1/0 (42.4 mm), Cable Plug 35	ALP1980472	9
TIG Torch 26	CAN-UWP26FX-25-0B-MSL-GS4-ZS	
MIG TORCH Tweco® Style 300A Consumable Standard Set	ALPCON4001	3
TIG Consumable Set for TIG TORCH 26 Series	ALPTORCHCON26	
Gas Fitting	CGA3180121	-169
Spool Holder Adapter 12" To 8"	CGA2890928	0
Argon/CO2 Regulator	CW-RMV-250-30LM-AR	00
C9 Black (Series Helmets)	CWPOWER-990T-BLK	•
C5 Black (Series Helmets)	CWELITE-550S-BLK	9
C8 Black (Series Helmets)	CWPOWER-980S-BLK	•
C8 Coal Fire (Series Helmets	CWPOWER-980S-CO	1